×



Item Number EB10751485

https://www.eibabo.uk/siemens/main-switch-3-pole-32a-11.5kw-400v-safety-switch-3-p-11-5kw-3ld225 4-0tk51-eb10751485



Main switch 3-pole 32A 11.5kW/400V - Safety switch 3-p 11,5kW 3LD2254-0TK51

Siemens

3LD2254-0TK51 4011209403239 EAN/GTIN

26,34 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Main switch 3p. 32A 11.5kW/400V 3LD2254-0TK51 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Number of switches 1 Max. rated operational voltage Ue at AC 690V Rated uninterrupted current lu 32A Rated uninterrupted current at AC-23, 400 V 22A, rated continuous current at AC-21, 400 V 32A, rated operational power at AC-3, 400 V 9.5kW, rated short-time withstand current lcw 0.64kA, rated operational power at AC-23, 400 V 11.5kW, number of poles 3, number of auxiliary contacts as NC contacts 0, Number of auxiliary contacts as NC contacts 0, Number of auxiliary contacts as changeover contact 0, Device type built-in device, fixed installation technology, Suitable for central front mounting, Color of the actuating element black, Design of the actuating element short rotary handle, Lockable, Connection type main circuit box terminal, Protection class (IP), on the front IP65, Protection class (NEMA) other, SENTRON, 3LD switch disconnector, main switch, 3-pole, lu: 32 A, operating power / at AC-23 A at 400V: 11.5 kW, front-mounted, rotary operator, black, central mounting 22.5mm of the handle The 3LD main and emergency stop switch as a repair switch for safely disconnecting loads in a wide variety of environments. The possible uses of the 3LD line disconnector are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD have proven themselves in many areas, especially in machining and processing machines in machine and conveyor system construction, in the chemical or in the food and beverage industry. The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches, N-PE terminal or 4th pole. 2. Versatile and can be used worldwide thanks to international IEC UL and shipbuilding approvals. 3. Degree of protection up to IP 65 with encapsulated housing for out

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

