



**LED spotlight black - Downlight/spot/floodlight
SUNAFLTR3700850MDBK**



ESYLUX
SUNAFLTR3700850MDBK
EL10810183
4015120810183 EAN/GTIN

105,48 GBP excl. VAT**
plus shipping



3-5 days* (GBR)

LED spotlight black SUNAFLTR3700850MDBK Suitable for surface mounting, Suitable for wall mounting, Adjustability rotatable and pivotable, With motion detector, With light sensor, LED illuminant not replaceable, With illuminant, Suitable for number of illuminants 1, Socket without, Housing material aluminium, Surface powder-coated, Housing color black, Cover material transparent glass, Type of voltage AC, Rated voltage 230 ... 230V, LED rated current at constant current 125 ... 273mA, Control gear LED control gear current-controlled, With control gear, Without dimming function, Reflector without, Light distributor diffuser lens/optics/- panel, symmetrical light distribution, beam angle extremely wide >80°, light emission direct, rated service life L70/B10 at 25 °C 45000h, rated service life L70/B50 at 25 °C 45000h, rated service life L80/B10 at 25 °C 30000h, rated service life L80/B50 at 25 °C 30000h, rated service life L90/B10 at 25 °C 15000h, rated service life L90/B50 at 25 °C 15000h, degree of protection (IP) IP65, protection class I, rated ambient temperature according to IEC62722-2-1 -25 ... 40°C, max. system power 28W, light color white, color temperature 5000 ... 5000K, Color rendering index CRI 80-89, luminous flux 3650 ... 3650lm, rated luminous flux according to IEC 62722-2-1 3650lm, width 227mm, height/depth 86mm, length 290mm, type of wiring suitable for through-wiring, number of positions 4, conductor cross-section 2.5mm², connectable Conductor cross-section 1.5 ... 2.5mm², connection type screw terminal, light output 130lm/W, LED spotlight made of high-quality die-cast aluminum housing and integrated motion detector with 160° detection range for convenient switching of the lighting. 30 W LED light output corresponds to 155 W incandescent lamp, light color 5000 K white. High light output with 130 lm/W. Very good color rendering index Ra 80. ADF special bracket made of stainless steel, additionally coated, for wall mounting inside and outside corners. Safe installation thanks to a separate connection box with easily accessible connection terminals. All external screws made of stainless steel. Rated service life L80B50 at 25 °C: 30000 h.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

