



Comb jumper 4x rated current 24A - Cross-connector for terminal block 4-p 2002-404



WAGO

2002-404

4055143687362 EAN/GTIN

0,65 GBP excl. VAT**

plus **shipping**



3-5 days* (GBR)

Comb jumper 4-fold rated current 24A 2002-404 version cross connector, number of bridged terminals 4, explosion-tested version "Ex e", rated current In 25A, rated voltage 800V, isolated, with protection against accidental contact, type of installation pluggable, pitch 5.2mm, color grey, Comb jumper isolated 4-fold, rated current 25 A, light grey

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



COMPLAINTS HANDLING

Obliging and 100% safely



SHORT DELIVERY TIME

Warehousing



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



25 YEARS OF EXPERIENCE

In worldwide mail order



REFUND

Within 14 days



DHL TRACK & TRACE

Shipment tracking



ORDER LIVE CHAT

With order history



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

