



Contact element 1 NO contact, front M22-K10



Eaton

M22-K10

216376

4015082163761 EAN/GTIN

3,21 GBP excl. VAT**

plus shipping



3-5 days* (GBR)

Contact element 1S, front M22-K10 Number of contacts as changeover contacts 0, number of contacts as make contacts 1, number of contacts as break contacts 0, number of error signal switches 0, rated operating current Ie at AC-15, 230 V 6A, design of the electrical connection screw connection, Design can be plugged in and integrated, mounting type: front mounting, socket without, contact element, standard/approval: UL/CSA, IEC, size: NZM1/2/3/4, connection technology: screw terminals, mounting: front mounting, contact configuration S = normally open: 1 S, protection class : IP20, connection to SmartWire-DT: no, connection type: single contact, description of tripped auxiliary switch HIA: General tripped message "+" when triggered by voltage release, overload release, short-circuit release and when using the residual current release due to residual current., Use with circuit breaker size NZM1, 2, 3 : A tripped auxiliary switch can be clipped into the circuit breaker., Use with circuit breaker size NZM4: Up to two tripped auxiliary switches can be clipped into the circuit breaker., Any combination of auxiliary switch types are possible., Not in conjunction with switch-disconnector PN..., Marking in the switch: HIA., Identification in the FI block: HIAFI., When using the tripped auxiliary switches in the FI block, the normally closed contact works as a normally open contact and the normally open contact works as a normally closed contact., Description Normal auxiliary switch HIN: Switches with the main contacts. Takes on signaling and interlocking tasks., Use with circuit breaker size NZM1: A normal auxiliary switch can be clipped into the circuit breaker., Use with circuit breaker size NZM2: Up to two normal auxiliary switches can be clipped into the circuit breaker., Use with circuit breaker size NZM3, 4: Up to three Normal auxiliary switches can be clipped into the circuit breaker., Any combination of auxiliary switch types are possible., Marking in the switch: HIN., When combined with remote drive NZM-XR..., the right-hand installation slot for normal auxiliary switch HIN can only be equipped with individual contacts., Can be used for: NZM1(-4), 2(-4), 3(-4), 4(-4), PN1(-4), 2(-4), 3(-4), N(S)1(-4), 2(-4), 3(-4), 4(-4), standards and regulations: IEC 60947-5-1

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



DHL TRACK & TRACE

Shipment tracking



COMPLAINTS HANDLING

Obliging and 100% safely



25 YEARS OF EXPERIENCE

In worldwide mail order



ORDER LIVE CHAT

With order history



SHORT DELIVERY TIME

Warehousing



REFUND

Within 14 days



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

