

## Item Number EB10713816

https://www.eibabo.uk/beckhoff/digital-output-terminal-8-channel-24vdc-fieldbus-digital-module-0-in-8-o ut-kl2408-eb10713816



## Digital output terminal 8-channel, 24VDC - Fieldbus digital module 0 In / 8 Out KL2408

×

**Beckhoff** 

KL2408 119440

**59,39 GBP** excl. VAT\*\*

plus **shipping** 



3-5 days\* (GBR)

Digital output terminal 8-channel, 24VDC KL2408 supply voltage at DC 24 ... 24V, type of supply voltage DC, number of digital inputs 0, number of digital outputs 8, type of digital output other, output current 0.5A, permissible voltage at the output 24 ... 24V, type of output voltage DC, short-circuit protection, outputs available, number of HW interfaces Industrial Ethernet 0, number of interfaces PROFINET 0, number of HW interfaces serial RS-232 0, number of HW interfaces serial RS-422 0, number of HW interfaces serial RS-485 0, number of HW interfaces serial TTY 0, number of HW interfaces parallel 0, number of HW interfaces wireless 0, number of HW interfaces USB 0, number of HW Other interfaces 1, supports protocol for other bus systems, system components, degree of protection (IP) IP20, design of the electrical connection springloaded connection, fieldbus connection via separate bus coupler possible, mounting rail mo ntage possible, explosion protection category for gas without, explosion protection category for dust without, width 12mm, height 100mm, depth 68mm, The digital output terminal switches the binary control signals of the automation device to the actuators at the process level in an electrically isolated manner. It is protected against polarity reversal and processes load currents with overload and short-circuit-proof outputs. The Bus Terminal contains eight channels whose signal status is indicated by LEDs. It is particularly suitable for space-saving use in the control cabinet. The connection technology is ideally suited for single-ended inputs. The prerequisite is that all components work with the same reference point as the bus terminal. The power contacts are interconnected. The outputs are fed via the 24 V power contact

## YOUR ADVANTAGES



**WORLDWIDE TRADE** Corporate video eibmarkt®



**COMPLAINTS HANDLING** Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



**DHL TRACK & TRACE** Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

