



Power contactor 1NC 5.5KW/400V,AC DILM12-01 (230V50HZ) - Magnet contactor 12A 230VAC 0VDC DILM12-...

Eaton
DILM12-01(230V50HZ)
276865
4015082768652 EAN/GTIN

32,93 GBP excl. VAT**
plus shipping

 3-5 days* (GBR)

Power contactor 1NC 5.5KW/400V,AC DILM12-01(230V50HZ) Rated control supply voltage Us at AC 50 Hz 230 ... 230V, Rated control supply voltage Us at AC 60 Hz 240 ... 240V, Rated control supply voltage Us at DC 0V, Type of voltage for actuation AC, Rated operational current Ie at AC-1, 400 V 22A, rated operational current Ie at AC-3, 400 V 12A, rated operational power at AC-3, 400 V 5.5kW, rated operational current Ie at AC-4, 400 V 7A, rated operational power at AC-4, 400 V 3kW, rated operational power NEMA 7.4kW, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NC contact 1, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, power contactor, application: power contactor for motors, Power contactors up to 170 A, 3-pole, Utilization category: AC-1: Non-inductive or weakly inductive load, resistance furnaces, AC-3: Squirrel-cage motors: starting, switching off during operation, AC-4: K Squirrel-cage motors: Starting, counter-current braking, reversing, jogging, Connection technology: screw terminals, Note: Also suitable for motors of efficiency class IE3, IE3-capable devices are marked with the logo on the packaging., Poles: 3-pin, rated operational current AC-3 380 V 400 V: Ie= 12 A, rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: Ith = Ie= 22 A, encapsulated: Ith= 18 A, rated operational current AC-1 conventional thermal current 1-pole open: Ith= 50 A, encapsulated: Ith= 45 A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V: P= 3.5 kW, 380 V 400 V: P= 5.5 kW, 660 V 690 V: P= 6.5 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 2 kW, 380 V 400 V: P= 3 kW, 660 V 690 V: P= 4.4 kW, Can be combined with auxiliary switch: DILA-XHI(V)..., Contact equipment NC = NC contact: 1 NC, Notes: Contact elements according to EN 50012., With mirror contact., Type of current AC/DC: AC actuation

YOUR ADVANTAGES

 **WORLDWIDE TRADE**
Corporate video eibmarkt®

 **COMPLAINTS HANDLING**
Obliging and 100% safely

 **SHORT DELIVERY TIME**
Warehousing

 **99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide

 **25 YEARS OF EXPERIENCE**
In worldwide mail order

 **REFUND**
Within 14 days

 **DHL TRACK & TRACE**
Shipment tracking

 **ORDER LIVE CHAT**
With order history

 **DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

