



**LED recessed spotlight 35gr - Downlight/spot/floodlight
1x15W FLIR 100.1040.35 si**



LTS

FLIR 100.1040.35 si

636584

4043544391667 EAN/GTIN

79,58 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

LED recessed spotlight 4000K 35Gr FLIR 100.1040.35 si Suitable for built-in installation, Adjustability pivotable, LED bulbs not replaceable, With bulbs, Suitable for number of bulbs 1, Other socket, Other housing material, Other surface, Housing color silver, Voltage type AC, Rated voltage 220 ... 240V, LED nominal current at constant current 350 ... 350mA, ECG control gear, with control gear, without dimming function, highly specular reflector, reflector light distributor, symmetrical light distribution, beam angle medium beam 21-40°, light emission direct, energy efficiency index (EEI) of the power supply other, Protection class (IP) IP20, Protection class (NEMA) other, Impact resistance IK01, Protection class III, Suitable for lamp power 15 ... 15W, Max. system power 15W, Light color white, Color temperature 4000 ... 4000K, Color rendering index CRI 80-89, Rated luminous flux according to IEC 62722-2-1 1400lm, lamp luminous efficacy 93.33lm/W, height/depth 92mm, outer diameter 80mm, installation height he/-depth 90mm, installation diameter 68mm, type of wiring termination, connection type other, lamp with limited surface temperature "D mark", lamp luminous efficacy 93.33lm/W, photobiological safety according to EN 62471 other, color consistency (McAdam ellipse) SDCM3, Recessed spotlight with optical design variants and a wide range of applications, light head can be swiveled by 20°, high ease of maintenance, no UV and thermal radiation, innovative heat management with passive cooling (heat sink made of die-cast aluminum), high-performance mirror reflector made of aluminum with precise symmetrical radiation characteristics for maximum light output and optimal glare control, Front/recessed ring made of die-cast zinc with clear light effect ring (further decor/light effect rings and decorative glasses are available as options), tool-free ceiling installation with quick-release springs (automatic adjustment of the ceiling thickness), connection to control gear via light cable with mini-clamp plug connection, control gear (LE D converter) included (placed externally)

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt[®]



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo[®] and eibmarkt[®] are registered trademarks of EIBMARKT[®] GmbH holding company (www.eibmarkt.de). eibabo[®] is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT[®] GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo[®] the Smart Home technology shop
eibabo[®] electronics cheap online order
eibabo[®] electric appliances buy online

